



Note on Packaging Unit (PU) and Subpackaging Unit (SPU): If you order a full PU, you will receive our eco-friendly, sustainable cardboard blisters packed in a shelf-ready box. If you order a quantity smaller than a full PU, you will receive the eco-friendly, sustainable cardboard blisters without a shelf-ready box.

Please refer to the system description for the splicing connectors that can be used.

Your benefits:

- Easy, fast and safe to use
- · Can be used immediately and accessed again later
- Silicon-free
- Label-free
- Suitable for indefinite storage
- The complete system consisting of WAGO's gelboxes and splicing connectors has been VDE-tested and IPX8-certified.

Physical data	
Width	40.1 mm / 1.579 inches
Height	21.3 mm / 0.839 inches
Depth	57 mm / 2.244 inches

Mechanical data	
Mounting type	Flying leads

Data sheet | Item number: 207-1433

https://www.wago.com/207-1433



Material data	
Note (material data)	Information on material data can be found here
Color	gray
Housing material	Polypropylene
Fire load	0 MJ
Weight	35.4 g

Environmental requirements	
Ambient temperature (operation)	-55 +85 °C
Surrounding air temperature (storage)	0+40 °C

Subject to changes. Please also observe the further product documentation!

Current addresses can be found at: <u>www.wago.com</u>