

## 818 CUR/L



Products may differ in size, colour and appearance to those shown. If you require further information or customisation, please contact us directly.

<b>Material</b>	Polycarbonate
<b>Protection class</b>	IP65
<b>Temp. range min</b>	-25 °C
<b>Temp. range max</b>	85 °C
<b>Glow wire test</b>	650 °C
<b>Impact resistance</b>	IK08
<b>External dimensions LxWxH</b>	215x200x95mm
<b>Type</b>	818 CUR/L
<b>UK-Number</b>	818 CUR/L
<b>Product Color</b>	RAL 7035
<b>WISKA-Order no.</b>	10111966
<b>Packing unit</b>	1

Description:

Suitable for relocating up to 10 ways\*

Fast self-tapping stainless screws

Terminals\*\*

2102-1201 - Grey 2 conductor DIN-rail terminal with Lever and Push-in up to 4mm

2102-1204 - Blue 2 conductor DIN-rail terminal with Lever and Push-in up to 4mm

2102-1207 - Green/Yellow 2 conductor DIN-rail terminal with Lever and Push-in up to 4mm

2102-1292 - Orange Endplate for 2102

2110-1201 - Grey 2 conductor DIN-rail terminal with Lever and Push-in up to 16mm

2110-1204 - Blue 2 conductor DIN-rail terminal with Lever and Push-in up to 16mm

2110-1207 - Green/Yellow 2 conductor DIN-rail terminal with Lever and push-in up to 16mm

2110-1292 - Orange Endplate for 2110

Your Contact:

**WISKA UK Ltd.**

Unit 7, Hurling Way · St. Columb Major Business Park · TR9 6SX, St. Columb Major, Cornwall · Great Britain

☎ +44-12-08816062 · 📠 +44-12-08816708

info@wiska.co.uk · www.wiska.co.uk

**\*Each Final ring circuit need to be considered as 2 ways**



**\*\*We reserve the right to use alternative push-in terminals to the same standard should there be supply issues.**

16.04.2023

Your Contact:

**WISKA UK Ltd.**

Unit 7, Hurling Way · St. Columb Major Business Park · TR9 6SX, St. Columb Major, Cornwall · Great Britain

 +44-12-08816062 ·  +44-12-08816708

info@wiska.co.uk · [www.wiska.co.uk](http://www.wiska.co.uk)

Other technical data on request / subject to change without notice